

# Checklist LO4-LEM1

## CODE LO4 LEM1 Category Tricycle Checklist

1<sup>st</sup> February 2006

### Owner Details

Owner's Name \_\_\_\_\_

Address \_\_\_\_\_

\_\_\_\_\_

Telephone \_\_\_\_\_ Mobile \_\_\_\_\_

Email \_\_\_\_\_

### Vehicle Details

Make \_\_\_\_\_ Model \_\_\_\_\_ Year of Manufacture \_\_\_\_\_

Vehicle Mass (kg) \_\_\_\_\_ Fuel Tank Certification Number (where applicable) \_\_\_\_\_

VIN/Chassis Number

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

### Engine Details

Make \_\_\_\_\_ Type \_\_\_\_\_ No. of Cylinders/Rotors \_\_\_\_\_

Displacement \_\_\_\_\_ Litres or \_\_\_\_\_ Cubic Inches \_\_\_\_\_ Year of Manufacture \_\_\_\_\_

ADR Engine was designed to comply with \_\_\_\_\_ Maximum Power Output \_\_\_\_\_ kW or \_\_\_\_\_ BHP

### Signatory Approval

Vehicle Approved By (Signatory) \_\_\_\_\_

Signatory Employer (if applicable) \_\_\_\_\_

### Signed

\_\_\_\_\_ Date \_\_\_\_\_



### ICV Tricycle Guidelines: LO4-LEM1 Checklist

FEATURE								
(1) FEATURE	(2) If 'E' Marked Approval NO	Height (#)		(5) APART	(6) EDGE	(7) G	(8) C	(9) R
		(3) MAX		(4) MIN	(#)	(#)	(*)	(*)
Main beam (*)				<200	Dipped beam	Dipped		Dipped
Dipped beam (*)		1200	500	<200	(a) <400	Main		Main
Direction Indicator Front (*)		1200	350	>240	(a) <400			
Direction Indicator Rear (*)		1200	350	>180	(b) <400			
Stop lamp(*)		1200	250	(b) >400		Rpos	Rpos	Rpos
Rr. Regisn. Plate lamp(*)						Rpos	Rpos	
Fr. Position lamp(*)		1200	350		<400 (a) <150 (c)	Dipped	Dipped	Dipped
Rr. position lamp (*)		1500	250	>400 (b)	<400 (b) <150 (c)	Stop	Stop	Stop
Reflex reflector Rear(*)		900	250	>400 (b)	<400 (b, c)	Rpos	Rpos	
Reflex reflector Side (*)		900	300					
Front fog lamp(+)		<Dipped Beam	250	<250 from c/l				
Rear fog lamp (+)		900	250	>100 form stop				
(*) = Mandatory (+) = If fitted; All dimension in mm. (#) = HEIGHT - To highest (Max) and lowest (Min) points on illuminating								

Notes:.....  
 .....  
 .....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

CLAUSE NO	FEATURE	COMPLIANCE	Sig
Apart – Distance between innermost edges of illuminating surface. EDGE – Maximum distance from outer edge of vehicle to illuminating surface. Column (7) to (9) indicates specific lamps which may be grouped (G), combined (C) or reciprocally incorporated (R).			
A.6.1	<b>DRIVING (MAIN) BEAM HEADLAMPS</b>		
A6.1.31	Geometric centre located in longitudinal media plane?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If NA is it's centre of reference symmetrical in relation to another driving/passing/front position lamp?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.1.3.3	Is the distance between the edges of the illuminating surface of any independent driving lamp and the edge of the passing lamp not more than 200mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.1.3.4	If 2 driving lamps fitted is the distance between the illuminating surfaces not more than 200mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.1.8	Non-flashing ("circuit-closed") tell- tail blue and operating?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.2	<b>PASSING BEAM (DIPPED) – HEADLAMPS</b>		
	Centre of lamp in longitudinal median plane?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.2.3.1.2	If NA is its centre of reference symmetrical in relation to another driving/passing/front position lamp?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.2.3.4	If 2 passing lamps fitted is the distance between the illuminating surfaces not more than 200mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.2.7	Are all driving beams switched 'OFF' when changing from driving to passing beam?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6 2.8	If fitted, is operational tell-tale colour green and non-flashing?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	<b>DIRECTION INDICATOR LAMP</b>		
	(1) Front indicators at least 240mm between illuminating surfaces?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3	(2) Front indicators outside vertical planes tangential to outside of headlamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.3.1	(3) Distance between the illuminating surface of the indicator and passing beam headlamp at least 75mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If NA Note distance between illuminating surfaces.....mm	<input style="width: 50px; height: 20px;" type="text"/>	

Notes:.....  
 .....  
 .....

**ICV Tricycle Guidelines: LO4-LEM1 Checklist**

A.6.3.3.1	Illuminating surfaces of rear indicators at least 180mm apart?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.3.3	Rear indicators within 300mm of rear end of vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.8	Independent switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Lamps on one side operated by one control?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.9	Operating Green or Yellow Tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If NA Is an audible operating tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If any direction indicator lamp defective, does tell-tale extinguish, remain alight without flashing, or shows marked change in frequency? Please circle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.10.1	Flash rate 60 –120 times per minute?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.10.2	Flash in phase on same side?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.10.3	Light up within 1 sec, and extinguishes within 1.5 sec?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.10.4	In the event of a failure, other than a short circuit, the other direction indicator on the same side continues to flash or remain alight?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.10.4	In the event of a failure, other than a short circuit, the other direction indicator on the same side continues to flash or remain alight?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.4 A.6.4.6	<b>STOP LAMP</b> Lighted on any front or rear service brake application?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.5 A.6.5.2	<b>REAR – REGISTRATION PLATE ILLUMINATING DEVICE</b> Illuminates registration plate area?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.6 A.6.6.1	<b>FRONT POSITION LAMP (IF FITTED, MANDATORY FOR 19/02)</b> One or Two lamps fitted?.	One <input type="checkbox"/> Two <input type="checkbox"/>	
A.6.6.6	Green ‘Circuit-closed’ tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If NA Instrument lights as tell-tale?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.7 A.6.7.1	<b>REAR POSITION LAMP</b> One or Two lamps fitted? Please circle number of lamps	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.7.6	If “Circuit-closed” tell-tale fitted, is it the same as front position lamp tell-tail?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
 .....  
 .....

**ICV Tricycle Guidelines: LO4-LEM1 Checklist**

A.6.8 A.6.8	<b>REAR REFLEX REFLECTOR, NON-TRIANGULAR</b> One or Two lamps fitted?	One <input type="checkbox"/> Two <input type="checkbox"/>	
A.6.9 A.6.9.2	<b>VEHICLE – HAZARD WARNING SIGNAL (OPTIONAL BUT REQUIRED IN ADR 67)</b> Separate control operates all direction Indicator lamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.9.3	(1)Circuit closed tell-tale provided?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) If single tell-tale, signal flashing red?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3)If separate, is tell-tail the same as direction indicators?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.9.4	Capable of activation with ignition 'OFF'?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.10 A.6.10.1	<b>FRONT FOG LAMP (OPTIONAL)</b> Are ONE or TWO lamps fitted?	One <input type="checkbox"/> Two <input type="checkbox"/>	
A.6.10.3.1	If fitted, is it on the median longitudinal plane or is the illuminating edge within 250mm of it?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.10.9	Possible to operate the fog lamp independently of the driving-beam and the passing-beam head lamp(s)?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.10.7	If fitted, tell-tale non-flashing green?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.11 A.6.11.1	<b>REAR FOG LAMP (OPTIONAL)</b> Are ONE or TWO lamps fitted?	One <input type="checkbox"/> Two <input type="checkbox"/>	
A.6.11.3.3	Distance from edge of stop lamp not less than 100mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.11.6	Can only light up when either the main-beam or the dipped-beam or the front fog lamp is switched on?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Rear fog lamp switch independent of the front fog lamp switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	With the rear fog lamps switched 'ON' does switching 'OFF' the position lamp, extinguish the it and does it remain 'OFF' until deliberately switched 'ON' again?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.11.7	Is an amber "Circuit-closed" non-flashing tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.12 A.6.12.1	<b>SIDE REFLEX REFLECTOR, NON-TRIANGULAR (OPTIONAL FOR VEHICLES CERTIFIED TO ECE R53/00)</b> Are ONE or TWO side reflectors fitted, per side?	One <input type="checkbox"/> Two <input type="checkbox"/>	

Notes:.....  
.....  
.....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

A.6.12.3.3	Positioned such that the reflector(s) are not be masked by the driver's or passenger's clothes?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1 7.1.2 7.1.3	<b>PARKING LAMP (OPTIONAL)</b> Arrangement, ONE or TWO at FRONT, ONE or TWO at REAR	One <input type="checkbox"/> Two <input type="checkbox"/> Front	
		One <input type="checkbox"/> Two <input type="checkbox"/> Rear	
	ON or to RIGHT or on EITHER side of the median longitudinal plane?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1.6	(1) Independent switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Possible to operate with the ignition in the 'OFF' position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1.7	If tell-tale fitted, is it impossible to confuse it with that for the front and rear position lamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.2	<b>REVERSING LAMP (ONLY IF REVERSE GEAR FITTED)</b> Is the lamp always lit when reversing gear engaged?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.2.6	(1) The device controlling starting and stopping the engine is in a position where the engine can operate?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) The engine is running?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.4 7.4.1 7.4.3	<b>FRONT REFLEX REFLECTOR NON-TRIANGULAR</b> Are ONE or TWO side reflectors fitted? Please circle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(1) If only one reflector fitted, the centre of reference is on the vehicle medium longitudinal plane?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) If two reflectors fitted, is the illuminating surface not more than 400mm from the extreme outer edge of the side car.	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
8.9	<b>CONSPICUITY LAMP (MANDATORY FOR VEHICLES CERTIFIED TO 19/01)</b> Are TWO conspicuity lamps fitted, or is conspicuity lamp incorporated in passing headlamp?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
8.9.9.1	Conspicuity lamp is lighted with engine running?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
.....  
.....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

<b>ADR 23/01 - PASSENGER CAR TYRES (IF FITTED)</b>			
<b>CLAUSE NO</b>	<b>FEATURE</b>	<b>COMPLIANCE</b>	<b>Sig</b>
23.2.3	For one tyre fitted, identify : (if tyre size is different front and rear, complete 1 FR & 1 Rr tyre.  (1) Manufacturer or trade mark (2) Tyre size, speed category and carcass construction symbols (3) Date Code	FR ..... TR..... FR ..... TR..... FR ..... TR.....	
23.2.2.1.2	At least 4 tread wear indicators?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
23.2.3	Each tyre labelled on both sides, except for 'Asymmetrical Tyres', which are at least labelled on the outer 'Sidewalls'?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
23.2.3.8	If tyre is 'Asymmetrical', outer face indicated?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
23.4	If 'E' marked R30, Approval No .....	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
<b>ADR 24/02 - TYRE AND RIM SELECTION (ONLY IF FITTED WITH PASSENGER CAR TYRES).</b>			
<b>CLAUSE NO</b>	<b>FEATURE</b>	<b>COMPLIANCE</b>	<b>Sig</b>
24.2.1.1	A placard of durable material permanently affixed to the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
24.2.1.1.	Placard contains the following:	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(1) For each nominated rim profile the recommended tyre size?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Recommended tyre pressures in kPa?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) Statement on load rating and speed category?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
24.2.5.1	All tyres fitted to the vehicle of the same type of 'Carcass' construction?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
24.2.5.4.1 24.2.5.4.2	Maximum load rating and speed category of tyre fitted equal to or greater than that on the placard?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
 .....  
 .....

## ICV Tricycle Guidelines: LO4-LEM1 Checklist

ADR 33/00 – BRAKE SYSTEMS FOR MOTORCYCLE AND MOPEDS (ALL L-CATEGORIES)			
CLAUSE NO	FEATURE	COMPLIANCE	Sig
33.2.1.1	Split (s) or independent (I) Indicate S or I.	<input style="width: 50px; height: 20px;" type="text"/>	
33.2.1.4	Lining visible either directly or indirectly?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.1.6	Brake controls readily accessible?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.1.7	Adequate provision made for adjustment?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.5.1	Separate reservoir compartment for each sub-system?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.5.3	Labelling satisfactory and located on or near brake fluid reservoir cap?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.3.0	If split service brake system, failure indicator lamp: (1) Fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.3.2	(2) Activation check satisfactory?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.3.5	(3) Labelling satisfactory?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.4	If single brake power unit, an audible device provided?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.6	If E marked, R78 Approval No	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
ADR 39/00 – EXTERNAL NOISE OF MOTOR CYCLES (NA to vehicles certified to ADR 83/00)			
CLAUSE NO	FEATURE	COMPLIANCE	Sig
39.2	<b>MARKING REQUIREMENTS</b>	<input style="width: 50px; height: 20px;" type="text"/>	
39.2.1	Silencing system components marked with:		
39.2.1.1	(1) Trade name or mark of manufacturer?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
39.2.1.2	(2) Trade description given by manufacturer?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
39.2.2	Markings clearly legible and appears indelible?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
39.3	<b>LABELLING REQUIREMENTS</b> Stationary noise test information and vehicle labelling satisfactory?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
ADR 42/03 - GENERAL SAFETY REQUIREMENTS			
CLAUSE NO	FEATURE	COMPLIANCE	Sig
7	<b>DIESEL ENGINES</b> Is device fitted to prevent inadvertent starting of engine?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
8	<b>STEERING SYSTEM</b>		
8.1.2	Do components essential to steering operation transmit energy by mechanical means only?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
8.1.1	Steering wheel located centrally or to the right?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
10.1.1	<b>ELECTRICAL WIRING</b> Supported at not more than 600mm intervals?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
10.1.2/3/4	Properly insulated, located and protected from chafing?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
 .....  
 .....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

12 12.1	<b>EXTERNAL OR INTERNAL PROTRUSIONS</b> Devoid of external or internal projections or sharp or pointed fittings?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
13.1	<b>FIELD OF VIEW</b> Driver's view on either side and in all directions in front of the vehicle unobstructed?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
15.3 15.3.3.1	<b>WHEEL GUARDS (MUDGUARDS)</b> Rear wheel guards covers wheel from a point vertically above the foremost part of the wheel to an arc rearwards, up to a line through the centre at or less than 45 degree to horizontal?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
15.3.3	Unless bodywork provides required protection, front wheel guards extend over rear quarter of wheel?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
21.2	<b>WARNING DEVICE AUDIBLE</b> Fitted with at least one horn with constant amplitude and frequency characteristics?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
<b>ADR 42/04 – GENERAL SAFETY REQUIREMENTS (ALL CATEGORIES FROM 1-JAN-2005)</b>			
CLAUSE NO	FEATURE	COMPLIANCE	Sig
6	<b>DEISEL ENGINE</b> Is device fitted to prevent an inadvertent starting of engine?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1.2	<b>STEERING SYSTEM</b> Do components essential to steering operation transmit energy by mechanical means only?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1	Steering wheel located centrally or to the right?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
9.1.1	<b>ELECTRICAL WIRING</b> Supported at not more than 600mm intervals?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
9.1.2/3/4	Properly insulated, located and protected from chafing?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
11.1.1/2/3	<b>EXTERNAL OR INTERNAL PROTRUSIONS</b> Devoid of external or internal projections or sharp or pointed fittings?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
12.1	<b>FIELD OF VIEW</b> Driver's view on either side and in all directions in front of the vehicle unobstructed?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
14.3.2	<b>WHEEL GUARDS (MUDGUARDS)</b> Are wheels fitted with guards, or permanent structure, that cover at least the 'Section Width' of the tyre, and designed as to protect other road users against thrown-up stones, mud, ice, snow and water?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
14.3.3.1	Do Rear wheel guards covers the wheel from a point vertically above the foremost part of the wheel to an arc rearwards up to a line through the centre at or less than 45 degree to horizontal?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
 .....  
 .....

**ICV Tricycle Guidelines: LO4-LEM1 Checklist**

14.3.3.2	Unless bodywork provides required protection, do front wheel guards extend over rear quarter of wheel?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
15	<b>BRAKE TUBING AND BRAKE HOSES</b> For any one brake hose (if fitted) identify (1) Location & (2) Markings .....		
15	Brake tubing and hoses fitted to prevent chafing, kinking or other mechanical damage?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
20.2	<b>WARNING DEVICE AUDIBLE</b> Fitted with at least one horn with constant amplitude and frequency characteristics?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
25.3.1	<b>TYRE AND RIM SELECTION</b> All tyres fitted to an 'Axle' are the same type of 'Carcass' construction?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

**ADR 57/00 - SPECIAL REQUIREMENTS FOR L-GROUP VEHICLES**

CLAUSE NO	FEATURE	COMPLIANCE	Sig	
57.2.2 57.2.2.1	<b>STEERING GEAR</b> Handlebars extends not less than 250mm and not more than 450 mm on each side of centre line?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2.2	Height of lowest part of handgrip above lowest part of upper surface of driver's seat <380mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2.3	Steering gear designed to prevent overlocking?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2.4	Horizontal distance from mid-point between head stem bearing to centre of front wheel <550mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2.5	Handlebars symmetrical and located centrally?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.3	<b>OPERATION AND LOCATION OF CONTROLS</b> (Circle non-compliance)			
CONTROL	LOCATION	OPERATION	COMPLIANCE	Sig
Manual clutch (*)	Left side Handlebar? (#)	Squeeze to disengage?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Gear change (Opt)	Left side Foot?	Up from first gear to select others?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Head Lamp (**)	Left side Handlebar?	Up – main beam, down – dipped and 'OFF-guard' provided if combined with on-off switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Horn	Left side Handlebar?	Push to activate?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Direction Indicator	Either Handlebar?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Ignition (Opt)		Anti-clockwise to 'OFF' from other positions?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Manual only fuel shut-off (Opt)		Off-forward, On-downwards, Reverse (if provided) – On-upwards?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
 .....  
 .....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

Twist grip throttle	Right side Handlebar?	Self-closing in clockwise direction to idle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Supplemental engine stop	Right side Handlebar?	Thumb operated	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Front Brake	Right side Handlebar?	Squeeze to activate?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
If Auto trans	Right side Foot/ Left side Handlebar?	Squeeze to activate?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

(\* ) – Hand lever or combined with gear change.

57.2.3.1.2	<b>OPERATION REQUIREMENTS</b> Without removal of the operator’s right hand from the throttle, are the following operations possible?			
	(1) Hand lever control of front brake		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Turn signal control (if on right handlebar)?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) supplemental engine stop?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
57.2.3.1.3	Without removal of the operator’s left hand from the handgrip, are the following operations possible?			
	(1) Hand lever control of clutch and push horn button?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Turn signal control (if on left handlebar)?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) Headlamp beam control?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

57.2.3.3 **CONTROL AND VISUAL INDICATOR DISPLAY IDENTIFICATION**  
If an item of equipment listed below is provided, is it and its control positions identified at least as specified (\*).

Item	Identification & Visibility	Position Identification *	Compliance	Sig
Ignition switch #		OFF?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Supplemental engine stop	Engine stop?	OFF, run?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Manual choke #	Choke?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Electric starter		Start?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Headlamp beam control	Lights?	Hi, Lo?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Horn	Horn?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Direction indicator	Turn?	L, R?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Main beam indicator	Main Beam?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
 .....  
 .....

**ICV Tricycle Guidelines: LO4-LEM1 Checklist**

Tachometer	RPM		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>
Fuel tank shut off Control #	Fuel?	<b>OFF, ON, RES?</b>	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>
Neutral Indicator	Neutral?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>
Speedometer	km/h only?	Major graduations at 10km/h intervals?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>

# - Visibility to seated driver not required.

\* - THE EQUIVALENT ISO SYMBOL IS AN ACCEPTABLE ALTERNATIVE.

57.2.4	<b>TRANSMISSION REQUIREMENTS (IF TRANSMISSION MANUAL)</b> Is disengagement possible at any engine speed?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>
57.2.5	<b>ELECTRICAL GENERATOR AND BATTERY</b> Fitted with a battery or generator?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>
57.2.6	<b>FOOT REST</b> Foot rest fitted for each seating position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>
57.2.8	<b>CHAIN GUARDS (IF CHAIN DRIVEN)</b> Front sprocket and upper free run of chain covered to >300mm rear of rear most footrest, or to a point vertically above the centre of the rear drive sprocket?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>
57.3	If E marked, R60 Approval No	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>

**ADR 61/02 - VEHICLE MARKING**

CLAUSE NO	FEATURE	COMPLIANCE	Sig
5 5.1	<b>VEHICLE IDENTIFICATION NUMBER</b> (1) Is the VIN clearly visible on an integral part of the vehicle and not easily removed?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2).If VIN is directly marked on an integral part of the vehicle, is the minimum height at least 7mm? If NO What is height of VIN? Indicate ..... mm	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) If VIN is on a separate plate, which in turn is permanently affixed to an integral part of the vehicle, is the minimum height at least 4mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7 7.1	<b>ENGINE NUMBER</b> Can a legible engine number be readily seen when the engine is installed in the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Is the engine number permanently stamped, cast, laser engraved or a combination of these on the main component of the engine?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Is the engine number satisfactorily located?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
9.9.1.2.1	<b>REGISTRATION PLATES</b> Is there provision to mount a rear number plate so that its centre is no lower than 300mm from the ground?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
 .....  
 .....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

#### ADR 67/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES (FOR LE ONLY)

- (1) If any item in column 1 is 'E' Marked note marking in Column 2.  
 (2) Audit at least 2 items for each of Columns 3 to 9 inclusive. Circle non-compliance's, otherwise tick.  
 (3) Indicate compliance status for table at end in space provided.

#### FEATURES

(1) FEATURE	(2) If 'E' Earmarked Approval NO	Height (#)	(5) APART		(6) EDGE	(7) G	(8) C	(9) R
		(3) MAX	(4) MIN	(#)	(#)	(*)	(*)	
Main beam (*) (CI 67.4.1)					(*) Dipped beam	Dip		Dip
Dipped beam (*) (CI 67.4.2)			1200	(*) 500	400	Main		Main
Front fog lamp (+) (CI 67.4.10)		<Dip. beam	250		400	%f		Main Swiv
Reversing Lamp (*) (CI 67.4.14)		1200	250			%r		
Direction Indicator Front (CI 67.4.3) (*)		1200	350	300 ≥ 100 MAIN OR DIP	400	%f		Park
Direction Indicator Rear (CI 67.4.3) (*)		1200	350	240	400	%r		Park
Direction Indicator side (CI 67.4.3) (*)								
Stop lamp (CI 67.4.4) (*)		1200	350	600/400 67.4.4.3.1.2		%r		RPos Park
Rr. Regisn. Plate lamp (CL 67.4.5) (*)						%r	%r	%r
Fr. Position (side) Lamp (CI 67.4.6) (*)		1500	350	Symmetrical	400	%f		%f
Rr. position (side) Lamp tail lamp (CI 67.4.7) (*)		1500	350	400	400	%r	Reg	Stop
Rear fog lamp (+) (CI 67.4.11)		1000	250	≥100 FROM STOP		%r	%r	
Parking Lamp (+) (CI 67.4.13)		1500	350		400	%		% f

Notes:.....  
 .....  
 .....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

Reflex reflector Rear (*) (CI 67.4.8)		900	350	400	400	%r		
(Non-triangular) Front (+) (CI 67.4.17)		900	350	Central Or 400	400	fpos		
Side(+) (CI 67.4.12)		900	350			%		
Conspicuity lamps (*) (CI 67.4.18)		1200	250	Symmetrical		%f	%f	%f indic

<p>G = 'Grouped Lamps' means devices having separate illuminating surfaces and separate light sources, but a common lamp body.</p> <p>C = 'Combined' means devices having separate illuminating surfaces, but a common light source and common lamp body.</p> <p>(*) = Mandatory; (+) = If fitted.</p> <p>(#) = HEIGHT - To highest (Max) and lowest (Min) points on illuminating surface.</p> <p>Apart – Distance between innermost edges of illuminating surface.</p> <p>EDGE – Maximum distance from outer edge of vehicle to illuminating surface.</p> <p>All dimension in mm.</p> <p>Column (7) to (9) indicates specific lamps which may be grouped (G), combined (C) or reciprocally incorporated (R).</p> <p>%f = Permitted with any other frontlamp.</p>	<p>R = 'Reciprocally Incorporated' means devices having separate light sources (or a single light source operating in different ways), but a common or partially common illuminating surface and a common lamp body.</p> <p>%r = Permitted with any other rear lamp.</p> <p>% = Permitted with any other lamp.</p> <p><del>Dip</del> = Permitted with Dipped Beam.</p> <p>Main = Permitted with Main Beam.</p> <p>Fpos = Permitted with Front Position Side lamps.</p> <p><del>Park</del> = Not permitted with Park Lamps.</p> <p>Park = Permitted with Park Lamps.</p> <p>Stop = Permitted with stop lamps.</p> <p>Rpos = Permitted with Rear Position Side Lamps.</p> <p>Reg = Permitted with Rear Registration Plate Lamp.</p> <p><del>bdie</del> = Not permitted with Indicator Lamps.</p>
---	--

CLAUSE NO	FEATURE	COMPLIANCE	Sig
67.3 67.3.1	<b>VISIBILITY</b> Are apparent surfaces of all lamps unobstructed by any parts of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3 67.3.5	<b>GENERAL SPECIFICATIONS</b> Are all lamps constituting a pair symmetrical?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3.9	No red light visible from the front and no white light (except reversing light) visible from the rear of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
 .....  
 .....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

67.3.10	Can all front and rear position lamps, the rear registration plate lamp, and the passenger car side lamps (if fitted) be only switched on and off together?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3.11	Is it not possible to switch on the main-beam, dipped-beam and front and rear fog lamps with out first switching on the lamps referred to in clause 67.3.10?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3.13.1	Are no lamps (other than driving, passing or front fog lamps) concealed?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3.13.2	Is it possible to move a concealed lighting device into the position of use, without the aid of tools, in the event of a defect?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.1	<b>MAIN-BEAM HEADLAMPS</b> Are all main beams switched off when changing over from main beam to dipped beam?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.1.3.1.1	For single dipped beam application with an independent main beam. Is this main beam mounted directly above or below the dipped beam with it geometric centre situated on the longitudinal median of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.1.3.1.2	For two dipped beam applications are the main beam lamps mounted no closer to the outside edge of the vehicle than the outer edge of the dipped beam headlamp?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.1.10	Circuit closed tell-tale colour blue and non-flashing?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.2.9.1	<b>DIPPED – BEAM HEADLAMPS</b> Control within easy reach of driver?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.2.10	If operational tell-tale fitted, is it green and non-flashing?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.2.3.1.1	For single lamp applications, is this lamp mounted with it geometric centre situated on the longitudinal median of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.3.1.1	<b>DIRECTION INDICATOR LAMPS LE1</b> (1) Front indicators at least 300mm apart?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Front indicators further apart than the outside surfaces of the headlamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) Front indicator lamps at least 100mm from the headlamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(4) Rear indicators not more than 400mm from the extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.3.3.2	Front indicators within 1,800mm of the front surface of the vehicle? (2,500mm if necessary to comply with visibility requirements).	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
.....  
.....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

67.4.3.9	<b>ALL VEHICLES</b> Independent switch and flash in phase?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.10	(1) Is a visible tell-tale' fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Tell-tale behaviour on turn signal malfunction?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(A) - Marked frequency change, (B) - Continuously on, or (C) – Continuously off (Indicate A, B, C, )?	<input style="width: 50px; height: 20px;" type="text"/>	
67.4.3.11.1.3	For DC supply indicators flash 60 to 120 times per minute?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.11.3.1	For AC supply, indicators flash 45-120 times per minute?	<input style="width: 50px; height: 20px;" type="text"/>	
67.4.3.11.1.3	Lights up within 1 second and extinguishes within 1.5 seconds?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.11.4	If one lamp fails (other than due to a short-circuit) do other lamps flash when actuated?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.4.9	<b>STOP LAMP</b> Lighted with any service brake application?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If fitted, is telltale non-flashing operational type?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.5	<b>REAR REGISTRATION PLATE LAMP</b> Illuminates the registration plate area?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.5	<b>FRONT POSITION LAMPS</b> <b>One</b> or <b>Two</b> lamps fitted in Dipped Beam headlamp? Please circle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Not further than 400mm from extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.6.3.1.2 67.4.9.3	Instrument lights as tell-tail?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If NA, is a non-flashing green tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.7.1.1	<b>REAR POSITION LAMP (RPL) LE1</b> Distance between illuminating surface at least 400mm, and within 400mm from extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.7.3.1.1	Instrument light as telltale?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.7.10	If NA, is a non-flashing green telltale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.8.3.1.2	<b>REAR REFLEX REFLECTOR (NON-TRIANGULAR) LE1</b> Distance between illuminating surface at least 400mm, and within 400mm from extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.8.3.1.1	<b>HAZARD WARNING LAMP</b> All direction indicator lamps flash in phase?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.9.1	Independent switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
.....  
.....

### ICV Tricycle Guidelines: LO4-LEM1 Checklist

67.4.9.2	Flashing telltale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.9.3	Can Hazard Warning be activated with engine ignition in the off position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.9.4.1	<b>FRONT FOG LAMPS (OPTIONAL)</b> <b>LE1</b>		
	Lamp centre of reference on the medium longitudinal plane or not more than 250mm from the medium longitudinal plane of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.10.3.1.2	<b>REAR FOG LAMPS (OPTIONAL)</b> If only one lamp fitted is mounted either in the median longitudinal plane or to the right?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.11.3.1	The illuminating surface of the fog lamp at least 100mm from the illuminating surface of the stop lamp?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.11.3.4	(1) Can rear fog lamp operate only when dipped beam or main beam lamps and/or the front fog lamp is on?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Can rear fog lamp be extinguished independently of the front fog lamps (if fitted)?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Independent, non-flashing, circuit closed tell-tale fitted and operational?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.11.9	<b>PARKING LAMP (OPTIONAL)</b> <b>For LB1, LE1</b> If rear oriented only, <b>One</b> or <b>Two</b> lamps fitted?	One <input type="checkbox"/> Two <input type="checkbox"/>	
	If front and rear oriented <b>Two</b> or <b>Three</b> lamps fitted?	Two <input type="checkbox"/> Three <input type="checkbox"/>	
67.4.13.2.2	Is illuminating surface not more than 400mm from extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If only two lamps provided are these provided on the side of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.13.9	Switch to permit parking lamps to be lit independently of any other lamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.13.9	Able to operate with the ignition switch in 'OFF' position	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.13.10	If fitted, impossible to confuse telltale with that for the front and rear position Lamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.14.9	<b>REVERSING LAMPS (IF REVERSE GEAR FITTED)</b> Is the lamp always lit when reverse gear engaged and:	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.14.9	(1) The device controlling starting and stopping engine is in a position where engine can be operated?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) The engine is running?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.18.3.1 67.4.18.11	<b>CONSPICUITY LAMPS (OPTIONAL)</b> Are <b>One</b> or <b>Two</b> conspicuity lamps fitted?	One <input type="checkbox"/> Two <input type="checkbox"/>	
	Are they <b>separate lamps</b> or <b>combined with Dipped-Beam headlamps</b> ?	Sep <input type="checkbox"/> Comb <input type="checkbox"/>	
67.4.18.9.1	If conspicuity Lamps fitted, are they lit every time the engine is run?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....  
.....  
.....

**ICV Tricycle Guidelines: LO4-LEM1 Checklist**

67.4.18.9.1	<b>CORNERING LAMPS (OPTIONAL)</b> Lighted continuously together with the corresponding direction indicator?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.19.9.2	Only lighted when the headlamp switch is in the on position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.20 67.4.20.4.3.2	<b>SIDE MARKER LAMPS (OPTIONAL, MANDATORY FOR VEHICLES &gt;2.1m WIDE and &gt; 7.5m in LENGTH)</b> Front lamps within the front 3 <sup>rd</sup> of the vehicle , but not forward of a plane through the rearmost point of the driver's seat in the rearmost position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.20.4.3.1	Are rear lamps not more than 300mm from the rear of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

**ADR 83/00 – EXTERNAL NOISE (New Models from 1-JAN-2005, All vehicles from 1-Jan-2006)**

CLAUSE NO	FEATURE	COMPLIANCE	Sig
B/C 4.1	<b>MARKING REQUIREMENTS</b> Silencing system components marked with:	.....	
B/C 4.1.1	(1) Trade name or mark of manufacturer?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
B/C 4.1.2	(2) Trade description given by manufacturer?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
B/C 4.2	Markings clearly legible and appears indelible?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
B 6.1 B 6.1.1	<b>LABELLING REQUIREMENTS</b> Is the following information provided on the motorcycle in an easily accessible (not necessarily immediately visible) location? (1) The manufacturer's name? (2) The value in dB(A) for the stationary noise test? (3) The engine speed in RPM?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If 'E' marked, R41 or R63 Approval No.....	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

**Additional Safety Requirements**

	Are welded steering or suspension components accompanied by a satisfactory report from a Signatory or Metallurgist?*	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	There are no critical steering or suspension components that have been chrome plated	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

**NOTE:** If the answer to any question is **N (No)**, the modification cannot be approved under this Code.

Notes:.....  
.....  
.....