



**Australian Government**

**Department of Infrastructure, Transport,  
Regional Development and Local Government**

**Department of Infrastructure, Transport,  
Regional Development and Local Government  
Vehicle Safety Standards Branch  
Road-Friendly Suspension Certificate Number (RFCN): RF2060  
Issue Date: 13 April 2017**

The Assistant Secretary, Vehicle Safety Standards Branch has assessed the information in Schedule 3 for the suspension described in Road Friendly Certificate Schedule 2, which the Supplier identified in Schedule 1 has submitted as complying with the road-friendliness requirements as specified in National Road Transport Commission (NRTC) publication 'Road-Friendly Suspension – Performance and Component Requirements, and Acceptable Test methods'. This information will be acceptable for use as evidence of compliance with the requirements specified in the NRTC publication provided the suspension is installed according to the Supplier's nominated installation instructions identified in Schedule 3.

The issue of this Certificate is subject to the following conditions:

1. The Supplier shall not quote the Road-Friendly Certificate Number in respect of a suspension which is not the suspension certified in the Road-Friendly Suspension certificate with that number.
2. Without the prior approval of the Assistant Secretary, Vehicle Safety Standards Branch, the Supplier shall not quote Road-Friendly Certificate Number in respect of a suspension, that is in any way different from the suspension described in the final form of the application for this Suspension Certificate Number. The application includes reports and other information relating to the application.
3. The Supplier shall by detailed quality control and test ensure continuing compliance with the requirements.
4. The Supplier shall maintain records of detailed quality control and test documentation.
5. The Supplier shall supply upon request, to Assistant Secretary, Vehicle Safety Standards Branch any additional information requested for the purpose of demonstrating compliance.
6. The Supplier shall not quote the Road-Friendly Certificate Number in respect of a suspension on or after the Expiry date specified in the certificate.
7. The Supplier shall indicate by an appropriate method (decal, label or plate) the Road-Friendly Suspension Certificate Number (RFCN) on the suspension system.
8. On cessation of marketing the specified suspension in Australia, the Supplier shall notify Assistant Secretary, Vehicle Safety Standards Branch of the date of manufacture of the last specified suspension supplied to the market in Australia.
9. If the requirements for road-friendliness are changed by the National Road Transport Commission, a new approval may be required.



**Australian Government**

**Department of Infrastructure, Transport,  
Regional Development and Local Government**

Certificate No: **RF2060**  
Issue Date: **13 April 2017**  
Expiry Date: **Life of Model**

**SCHEDULE 1**

**Supplier Name:** Maxitrans      **Supplier ID:** L1925

**Supplier Address:** 233-243 Learmonth Road  
Wendouree VIC 3355

**SCHEDULE 2**

**Make:** MAXITRANS

**Model:** AIRMAX 011

**SCHEDULE 3**

	Variant 1	Variant 2	Variant 3	Variant 4
Variant name:	AIRMAX 1	AIRMAX 2	AIRMAX 5	AIRMAX 9
Number of Axles	2	2	2	2
Overslung/Underslung	OVERSLUNG	OVERSLUNG	UNDERSLUNG	OVERSLUNG
Maximum Axle spread (m)	2.000	2.000	2.000	2.000
Dampers Part Numbers	Koni 912641SP1	27501	27501	Powerdown SPP969
Smallest Tyre Size Designation	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5
Highest tyre pressure (Kpa)	825	825	825	825
Airbag Diameter (mm)	338	338	338	338
Reference Drawings No of Suspension (parts list & assembly details)	804384	804384	5075790	5075790



**Australian Government**

**Department of Infrastructure, Transport,  
Regional Development and Local Government**

	Variant 5	Variant 6	Variant 7	Variant 8
Variant name:	AIRMAX 10	AIRMAX 3	AIRMAX 4	AIRMAX 6
Number of Axles	2	3	3	3
Overslung/Underslung	UNDERSLUNG	OVERSLUNG	OVERSLUNG	UNDERSLUNG
Maximum Axle spread (m)	2.000	3.200	3.200	3.200
Dampers Part Numbers	Powerdown SPP969	Koni 912641SP1	27501	27501
Smallest Tyre Size Designation	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5
Highest tyre pressure (Kpa)	825	825	825	825
Airbag Diameter (mm)	338	338	338	338
Reference Drawings No of Suspension (parts list & assembly details)	5075790	804384 & 5075954	804384 & 5075954	5075954

	Variant 9	Variant 10	Variant 11	Variant 12
Variant name:	AIRMAX 11	AIRMAX 12	AIRMAX 7	AIRMAX 8
Number of Axles	3	3	4	4
Overslung/Underslung	OVERSLUNG	UNDERSLUNG	OVERSLUNG	UNDERSLUNG
Maximum Axle spread (m)	3.200	3.200	4.000	4.000
Dampers Part Numbers	Powerdown SPP969	Powerdown SPP969	27501	27501
Smallest Tyre Size Designation	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5
Highest tyre pressure (Kpa)	825	825	825	825
Airbag Diameter (mm)	338	338	338	338
Reference Drawings No of Suspension (parts list & assembly details)	5075790	5075790	5075954	5075954



**Australian Government**

**Department of Infrastructure, Transport,  
Regional Development and Local Government**

	Variant 13	Variant 14		
Variant name:	AIRMAX 13	AIRMAX 14		
Number of Axles	4	4		
Overslung/Underslung	OVERSLUNG	UNDERSLUNG		
Maximum Axle spread (m)	4.000	4.000		
Dampers Part Numbers	Powerdown SPP969	Powerdown SPP969		
Smallest Tyre Size Designation	215/75R17.5	215/75R17.5		
Highest tyre pressure (Kpa)	825	825		
Airbag Diameter (mm)	338	338		
Reference Drawings No of Suspension (parts list & assembly details)	5075954	5075954		

*Umesh Shamdasani*

**Heavy Vehicle Certifications**

**Date: 13 April 2017**